



Printed 3/19/2024

**Z0777**

## TECHNICAL SERVICE BULLETIN

### POLYCHEM<sup>®</sup> 7563-V-60

POLYCHEM<sup>®</sup> 7563-V-60 is a vinyl toluene copolymer designed for use in primers, enamels, aerosols, and sanding sealers where lacquer type dry is required. This product is low-HAP and can be formulated into HAP-free coatings (below 1% HAP).

<u>CHARACTERISTIC</u>	<u>SPECIFICATIONS</u>
NVM%	59 - 61
VISCOSITY, G-H	Y - Z1
SOLVENT	VM&P
POUNDS PER GALLON	7.4 +/- 0.1
ACID NUMBER (NVM)	4 MAX
GARDNER COLOR	4 MAX
REDUCED VISCOSITY	C - F
REDUCED NVM	40
REDUCED SOLVENT	VM&P
OIL	Linseed Oil
CLARITY	CLEAR TO SLIGHTLY HAZY

### APPLICATIONS

Equipment enamels  
Floor sealers

### DRIER RECOMMENDATIONS (% METAL ON TOAL BINDER SOLIDS):

Cobalt	0.05%
Manganese	0.03%
Zirconium	0.50%

The information and specifications stated here are for the material currently offered, are subject to change without prior notice, and due to variations in user handling and application methods should not be relied upon without testing under user conditions. The supplier makes no warranty of any kind, express or implied, concerning this product or its use, either singly or in combination with other substances. User assumes all risks incident to its use. User must communicate to employees and customers all warnings that relate to the potential exposure to this product. The user assures that all workplace and disposal practices are in compliance with laws, regulations and ordinances. ALL WARRANTIES, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE,

Form Revision 04/01/16

Revision Date 7/10/2003

**1920 LEONARD AVENUE COLUMBUS OH 43219**  
**PHONE (614) 253-8511 EMAIL - [info@opcpolymers.com](mailto:info@opcpolymers.com)**