



TECHNICAL SERVICE BULLETIN

ECO-ALKYD® 7639-TBA-60

ECO-ALKYD® 7639-TBA-60 is a chain stopped TOFA alkyd formulated for use in fast drying durable finishes. This product is thinned in t-Butyl Acetate version of 6868 and used for very low VOC formulations.

<u>CHARACTERISTIC</u>	<u>SPECIFICATIONS</u>
NVM%	59 - 61
VISCOSITY, G-H	Z - Z2
SOLVENT	t-Butyl Acetate
POUNDS PER GALLON	8.5 +/- 0.1
ACID NUMBER (NVM)	14 MAX
GARDNER COLOR	6 MAX
REDUCED VISCOSITY	L - P
REDUCED NVM	50
REDUCED SOLVENT	t-Butyl Acetate
CLARITY	10 Max

APPLICATIONS

Air dry or bake enamels

DRIER RECOMMENDATIONS (% METAL ON TOAL BINDER SOLIDS):

Cobalt	0.05%
Zirconium	0.40%

The information and specifications stated here are for the material currently offered, are subject to change without prior notice, and due to variations in user handling and application methods should not be relied upon without testing under user conditions. The supplier makes no warranty of any kind, express or implied, concerning this product or its use, either singly or in combination with other substances. User assumes all risks incident to its use. User must communicate to employees and customers all warnings that relate to the potential exposure to this product. The user assures that all workplace and disposal practices are in compliance with laws, regulations and ordinances. ALL WARRANTIES, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE,