



TECHNICAL SERVICE BULLETIN

POLYCHEM[®] 7776-PP-75

POLYCHEM[®] 7776-PP-75 is a HAPs free high solids fast drying water-reducible alkyd resin. It is ideal for industrial and high gloss DTM applications. It has excellent corrosion resistance and gloss retention along with great adhesion.

<u>CHARACTERISTIC</u>	<u>SPECIFICATIONS</u>
NVM%	74 - 76
VISCOSITY, G-H	Z6 - Z8
SOLVENT	Propylene Glycol Mono-Propylether
POUNDS PER GALLON	9 +/- 0.1
ACID NUMBER (NVM)	37 - 43
GARDNER COLOR	8 MAX
CLARITY	CLEAR

APPLICATIONS

High Quality Exterior Enamel
Industrial Top Coat
Primer Application
Industrial Maintenance Application

DRIER RECOMMENDATIONS (% METAL ON TOAL BINDER SOLIDS):

Cobalt - 0.03 - .0.05%
Zirconium - 0.20 - 0.35%
Calcium - 0.05 - 0.10%

The information and specifications stated here are for the material currently offered, are subject to change without prior notice, and due to variations in user handling and application methods should not be relied upon without testing under user conditions. The supplier makes no warranty of any kind, express or implied, concerning this product or its use, either singly or in combination with other substances. User assumes all risks incident to its use. User must communicate to employees and customers all warnings that relate to the potential exposure to this product. The user assures that all workplace and disposal practices are in compliance with laws, regulations and ordinances. ALL WARRANTIES, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE,