



TECHNICAL SERVICE BULLETIN

POLYCHEM[®] 7779-MS16-60

POLYCHEM[®] 7779-MS16-60 is a soybean oil modified uralkyd that exhibits fast dry, high gloss and water, mar and abrasion resistance.

<u>CHARACTERISTIC</u>	<u>SPECIFICATIONS</u>
NVM%	59 - 61
VISCOSITY, G-H	Z1 - Z3
SOLVENT	Mineral Spirits 16
POUNDS PER GALLON	7.66 +/- 0.1
ACID NUMBER (NVM)	2 MAX
GARDNER COLOR	6 MAX
REDUCED VISCOSITY	S - V
REDUCED NVM	55
REDUCED SOLVENT	Mineral Spirits 16
OIL	Soybean Oil
CLARITY	Clear to Slightly Hazy

APPLICATIONS

Clear and pigmented floor finishes, maintenance primers and enamels.

DRIER RECOMMENDATIONS (% METAL ON TOAL BINDER SOLIDS):

Cobalt	0.02%
Calcium	0.08%
Zirconium	0.20%

Cobalt Free Option

Calcium	0.1%
Zirconium	0.3%
Super Dry 1000	0.7%

The information and specifications stated here are for the material currently offered, are subject to change without prior notice, and due to variations in user handling and application methods should not be relied upon without testing under user conditions. The supplier makes no warranty of any kind, express or implied, concerning this product or its use, either singly or in combination with other substances. User assumes all risks incident to its use. User must communicate to employees and customers all warnings that relate to the potential exposure to this product. The user assures that all workplace and disposal practices are in compliance with laws, regulations and ordinances. ALL WARRANTIES, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE,