



Printed 4/17/2025

**Z8850**

## TECHNICAL SERVICE BULLETIN

### POLYCHEM<sup>®</sup> 7662-100

POLYCHEM<sup>®</sup> 7662-100 is a long oil soya alkyd designed for use with latex in exterior house paints. It is recommended to be used in the 20% resin solids range to improve adhesion and water resistance. This product is HAP-free.

<u>CHARACTERISTIC</u>	<u>SPECIFICATIONS</u>
NVM%	98 - 100
VISCOSITY, G-H	Z - Z2
POUNDS PER GALLON	8.51 +/- 0.1
ACID NUMBER (NVM)	10 MAX
GARDNER COLOR	6 MAX
REDUCED VISCOSITY	C - F
REDUCED NVM	70
REDUCED SOLVENT	Mineral Spirits, Low Aromatic
OIL	Soybean Oil
CLARITY	10 max

### DRIER RECOMMENDATIONS (% METAL ON TOAL BINDER SOLIDS):

Cobalt      0.05%

The information and specifications stated here are for the material currently offered, are subject to change without prior notice, and due to variations in user handling and application methods should not be relied upon without testing under user conditions. The supplier makes no warranty of any kind, express or implied, concerning this product or its use, either singly or in combination with other substances. User assumes all risks incident to its use. User must communicate to employees and customers all warnings that relate to the potential exposure to this product. The user assures that all workplace and disposal practices are in compliance with laws, regulations and ordinances. ALL WARRANTIES, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE,

Form Revision 04/01/16

Revision Date 2/2/2007

**1920 LEONARD AVENUE COLUMBUS OH 43219**  
**PHONE (614) 253-8511 EMAIL - [info@opcpolymers.com](mailto:info@opcpolymers.com)**